



# COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER



## Description

COMPACT C32 WP is a multipurpose two-way point source speaker, suitable for a wide range of near and mid-distance applications. The combination of a 3" neodymium compression driver, a 12" neodymium woofer, and a constant directivity rotatable waveguide produces coherent 100° x 50° coverage for the listening area with high SPL, and distortion-free sound. The sleek and lightweight wood cabinet uses a special polyurea coating and a robust powder-coated grille with protective foam. Optional mounting accessories allow for wall or ceiling installation. Suitable for outdoor applications. EN 54-24:2008 technical data available in the user manual.

## Features

- › 600 W power handling (RMS)
- › 137 dB max SPL
- › 54 ÷ 20000 Hz frequency range
- › 100° x 50° constant directivity coverage angle
- › 1 x 12" high power neodymium woofer
- › 1 x 3.0" v.c. neodymium compression driver
- › High quality birch plywood cabinet
- › Steel grille with water-repellent protection
- › Installation points available on top, bottom, rear and side panels
- › 2 x eco|mate IP 67 connectors

## Part Number

13000911 COMPACT C 32 WP 8ohm


Black - RAL 9005 EAN 8024530022822



# COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER

Line Art 2D



## TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB)	54 Hz - 20000 Hz
	Max SPL @ 1m	137 dB
	Horizontal coverage angle	100°
	Vertical coverage angle	50°
	Directivity index Q	10
	System Sensitivity	97 dB
Power section	Amplification	Full Range
	Nominal Impedance	8 ohm
	Power Handling	600 W RMS
	Peak Power Handling	2400 W PEAK
	Protections	Dynamic Active Mosfet
	Crossover Frequencies	1100 Hz
Transducers	Recommended Amplifiers	XPS 16K, XPS 16KD, QPS 10K, QPS 6.0K, IPS 5.0K, IPS 2.5K, IPS 1.5K, DMA 504
	Compression Driver	1 x 1.4" neo, 3.0" v.c
Input/Output section	Woofers	1 x 12" neo, 3.5" v.c
	Input connectors	Amphenol eco/mat IP 67
Standard compliance	Output connectors	Amphenol eco/mat IP 67
	IP protection grade	IP 55
	Safety agency	CE compliant
	EN54-24 certified	Yes
CPR number	0068-CPR-234/2025	



# COMPACT C 32 WP

TWO-WAY PROFESSIONAL SPEAKER

Physical specifications	Cabinet/Case Material	Birch plywood		
	Hardware	4 x M8, 14 x M10		
	Grille	Steel grille with water-repellent protection		
	Color	Black - RAL 9005		
Size / Weight	Height	620 mm / 24.41 inches		
	Width	361.8 mm / 14.24 inches		
	Depth	404 mm / 15.91 inches		
	Weight	23.5 kg / 51.81 lbs		
Rigging / Mounting	<b>ACCESSORIES</b>			
	<b>FLYING BRACKETS</b>			
	13360742	FLB60742	Black	EAN 8024530024888
	<b>HORIZONTAL BRACKETS</b>			
	13360703	HBR60703	Black - RAL 9005	EAN 8024530023843
	<b>VERTICAL BRACKETS</b>			
	13360533	V-BR 002	Black - RAL 9005	EAN 8024530021320
	<b>WALL MOUNT BRACKETS</b>			
	13360539	WM-BR 001	Black - RAL 9005	EAN 8024530021344
	Upgrade Kits	<b>HORN KIT</b>		
13360505		HN-KIT COMPACT C 32 C 45	Black	EAN 8024530020019