

Datasheet

Model	iSwitch 265K
Name	Zero-Configuration 4K AV over IP w/ Video Wall & Visual Control

Video (iSwitch 265K-T)

Input Port	1 x HDMI
Input Resolutions	Up to 3840x2160p@30Hz
Output Port	1 x LAN
Output Resolutions	Up to 3840x2160p@30Hz
Video Protocol	H.264/H.265

Video (iSwitch 265K-R)

Input Port	1 x LAN
Input Resolutions	Up to 3840x2160p@30Hz
Output Port	1 x HDMI
Output Resolutions	Up to 3840x2160p@30Hz
Video Protocol	H.264/H.265
Audio Format	MPEG4-AAC Stereo

Audio (iSwitch 265K-T)

Input Port	1 x HDMI
Output Port	1 x LAN, 1 x Audio Out

Audio (iSwitch 265K-R)

Input Port	1 x LAN
Output Port	1 x HDMI, 1 x Audio Out
Audio Format	MPEG4-AAC Stereo

Control

Control Method	VDirector App (IOS/Android/Windows Version)
----------------	---------------------------------------------

General

Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
Storage Temperature	4°F ~ 158°F (-20°C ~ 70°C) 10% ~ 90%, non-condensing
Power Supply	DC12V 1A / PoE
Power Consumption (Max)	DC 12V: 3.6W PoE: 4.3W
ESD Protection	Human body model: ±8kV (air-gap discharge)/±4kV (contact discharge)
Product Dimensions	175mm x 25mm x 100.2mm / 6.9" x 0.98" x 3.9" (W x H x D)
Net Weight	0.60kg/1.32lbs