Scan to go to website

Modules List Quick Start Guide

This guide lists all available modules applicable for your T-IN1-RND1 & T-IN2-RND2 series and T-IN2-REC1, T-IN4-REC1, T-IN6-REC1 & T-IN2-REC2, T-IN4-REC2, T-IN6-REC series.

Go to https://www.kramerav.com/ to check for the latest documentation and check if firmware upgrades are available.

Modules List

All modules are available in two colors: Black – RAL 9011 / White RAL 9002

Model	Color	Description	Size & Weight		Specs	Figure
Power Socket Modules (MP)						
MP-U	80-000345 (B) 80-000344 (W)	Universal Power Socket	Product	50 x 50 x 130mm (1.96" x 1.96" x 5.11")	Input -100-240V~, 50/60Hz. Fuse - T 6.3A 250V Output – Maximum 6.3A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		
MP-US (Type B)	80-000347(B) 80-000346 (W)	American power socket Good for Japan	Product	50 x 50 x 130mm (1.96" x 1.96" x 5.11")	Input -100-240V~, 50/60Hz. Fuse - T 6.3A 250V Output – Maximum 6.3A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		
MP-DE (Type F)	80-000349 (B) 80-000348 (W)	Germany (Western Europe) power socket	Product	50 x 50 x 130mm (1.96" x 1.96" x 5.11")	Input -100-240V~, 50/60Hz. Fuse - T 6.3A 250V Output – Maximum 6.3A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		
MP-GB (Type G)	80-000351 (B) 80-000350 (W)	United Kingdom power socket	Product	75 x 75 x 181mm (2.95" x 2.95" x 7.12")	Input -100-240V~, 50/60Hz. Fuse - T 6.3A 250V Output – Maximum 6.3A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		


Manufacturer: Kramer Israel
2 Negev St. Airport City 7019900
+972 (0)73-265-0200
info_il@kramerav.com

EU Importer: Kramer EMEA Netherlands
Stroombaan 16, The Garden 1181VX
Amstelveen
info_EMEA@kramerav.com
P/N: 2900-301806QS Rev: 9

MP-IL (Type H)	80-000385 (B) 80-000386 (W)	Israel power socket	Product	75 x 75 x 181mm (2.95" x 2.95" x 7.12")	Input -100-240V~, 50/60Hz. Fuse – 10 A 250V Output – Maximum 10A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		
MP-SA (Type D)	80-000401 (B) 80-000402 (W)	South Africa power socket	Product	75 x 75 x 181mm (2.95" x 2.95" x 7.12")	Input -100-240V~, 50/60Hz. Fuse - T 6.3A 250V Output – Maximum 6.3A per power outlet	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.1 KG 0.22 Lb.		
Charging Modules (MC)						
MC-2C130W[1&2]	80-000340 (B) 80-000341 (W)	2 ports USBC 130W (65W when both ports connected).	Product	50 x 50 x 130mm (1.96" x 1.96" x 5.11")	**Output** C1 only: 100W Max C2 only: 100W Max C1 + C2: 65W+65W, 130W Max Input: 100-240V~, 50/60Hz, 2.5A Contains groove on one side only. For T-IN2-REC 2, insert either MC-2C130W or MC-C65W/A18W; but not both. T-IN-REC 1 series can be inserted first. The direction it faces will depend on the direction of the groove.	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.5KG 1.1Lb.		
MC-C65W/A18W[1&2]	80-000342 (B) 80-000343 (W)	USBC 65W port and USBA 18W port	Product	50 x 50 x 130mm (1.96" x 1.96" x 5.11")	**Output** USB-A – 18W Q.C 3.0 certified USB-C – 65W USB-A+USB-C: 18W+65W, 83W Max Input: 100-240V~, 50/60Hz, 1.8A Contains groove on one side only. For T-IN2-REC 2, insert either MC-2C130W or MC-C65W/A18W; but not both. T-IN-REC 1 series can be inserted first. The direction it faces will depend on the direction of the groove.	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.3KG 0.66Lb.		

[1] *Charging will start promptly, with a brief adjustment period due to different computer brand protocols."*
[2] *This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

Data Modules (MD)						
MD-2C/2CM	80-000353 (B) 80-000352 (W)	Passive module with 2 USBC FF ports input - Female. Output – Male pigtail cable 40cm long	Product	50 x 50 x 60mm (1.96" x 1.96" x 2.36")	Full feature - 4K@60 (4:4:4); 10Gbps 100W power charging.	
			Package	75 x 75 x 181mm (2.95" x 2.95" x 7.12")		
			Weight	0.05KG 0.11 Lb.		
MD-C/CM	80-000357 (B) 80-000356 (W)	Passive module with 1 USBC FF port input - Female. Output – Male pigtail cable 40cm long	Product	50 x 25 x 60mm (1.96" x 0.98" x 2.36")	Full feature - 4K@60 (4:4:4);	
			Package	75 x 75 x 90mm (2.95" x 2.95" x 3.54")	10Gbps; 100W power charging.	
			Weight	0.05KG 0.11 Lb.	Does not contain grooves ⓘ Cannot be inserted first for all T-IN-REC series.	
MD-H+B/AF	80-000358 (B) 80-000359 (W)	Passive module with 1 HDMI port + 1 USBB port input - Female. Output - HDMI + USBA – Female.	Product	50 x 25 x 60mm (1.96" x 0.98" x 2.36")	Input - USB-B 3.0 - Female connector	
			Package	75 x 75 x 90mm (2.95" x 2.95" x 3.54")	Output-USB-A 3.0 – Female connector ⓘ LED is turned On only when starting transmission	
			Weight	0.056KG 0.12 Lb.	HDMI – Female to Female	
MD-H/HF	80-000358 (B) 80-000359 (W)	Active module with 1 HDMI port. Input – Female HDMI Output – Female HDMI	Product	50 x 25 x 60mm (1.96" x 0.98" x 2.36").	Input - HDMI - Female connector	
			Package	75 x 75 x 90mm (2.95" x 2.95" x 3.54")	Output-HDMI – Female connector	
			Weight	0.03 kg (0.11 lb.)		

MD-2RJ45	80-000373 (B) 80-000372 (W)	Passive module with 2 RJ45 ports input. 2 female outputs.	Product	50 x 25 x 60mm (1.96" x 0.98" x 2.36")	S/FTP CAT6a	
			Package	75 x 75 x 90mm (2.95" x 2.95" x 3.54")		
			Weight	0.1KG 0.22 Lb.		
Pass-through / General modules						
MCP-1	80-000362 (B) 80-000363 (W)	Pass-through module with 1 hole. Accommodates cables up to 9mm in diameter.	Product	50 x 50 x 45mm (1.96" x 1.96" x 1.77")	Kramer recommends placing in the middle for T-IN4-REC1, T-IN6-REC1, T-IN4-REC2, T-IN6-REC2. When having more than 1 pass-through with retractor, Kramer recommends separating them from each other.	
			Package	50 x 50 x 130mm (1.96" x 1.96" x 5.11")		
			Weight	0.05KG 0.11 Lb.		
MCP-2	80-000360 (B) 80-000361 (W)	Pass-through module with 2 holes. Accommodates cables up to 9mm in diameter.	Product	50 x 50 x 45mm (1.96" x 1.96" x 1.77")	Kramer recommends placing in the middle for T-IN4-REC1, T-IN6-REC1, T-IN4-REC2, T-IN6-REC2. When having more than 1 pass-through with retractor, Kramer recommends separating them from each other.	
			Package	50 x 50 x 130mm (1.96" x 1.96" x 5.11")		
			Weight	0.05KG 0.11 Lb.		
MCP-3	80-000391 (B)	Pass-through module with 1 hole. Accommodates cables up to 9.5mm in diameter.	Product	50 x 50 x 61.7mm (1.96" x 1.96" x 2. 42")	Kramer recommends placing in the middle for T-IN4-REC1, T-IN6-REC1, T-IN4-REC2, T-IN6-REC2. When having more than 1 pass-through with retractor, Kramer recommends separating them from each other.	
			Package	75 x 12 x 76mm (2.95" x 4.7" x 2.99")		
			Weight	0.05KG 0.11 Lb.		
M-BLANK	80-000366 (B) 80-000367 (W)	Blank module.	Product	50 x 25 x 60mm (1.96" x 0.98" x 2.36")	Does not contain grooves Cannot be inserted 1st for all T-IN-REC series.	
			Package	50 x 50 x 130mm (1.96" x 1.96" x 5.11")		
			Weight	0.02KG 0.04 Lb.		