MD–C/CM

Passive module with 1 USBC FF port input



Our new TBUS product line offers a wide array of modules, designed to provide seamless connectivity and enhance the functionality of any meeting space. With our versatile selection, you can easily customize your tabletop connectivity solutions to meet specific requirements, ensuring a neat and efficient workspace. These components are crafted to integrate effortlessly into the TBUS system.
Available in two elegant colors — Graphite Black (RAL 9011) and Broken White (RAL 9002) — these modules provide the flexibility to create a tailored setup that keeps your workspaces organized and your connections reliable.
Explore the variety of options below to create a tailored setup that keeps your workspaces organized and your connections reliable

TECHNICAL SPECIFICATIONS

General	Overview Passive module with 1 USBC FF port input
	Input Female USB–C Connector
	Output Male pigtail cable 40cm long
	Weight 0.05 kg (0.11 lb.)
	Video 4K@60 (4:4:4)
	Data 10Gbps USB 3.2 Gen 2
	Power 100W power charging



CONFIGURATIONS

MD–C/CM(B)	Passive module with 1 USBC FF port. Input — Female USB–C Connector. Output — Male pigtail cable 40cm long. Dimensions -50 x 25 x 60mm (1.96" x 0.98" x 2.36"). Weight — 0.05 kg (0.11 lb.)
MD–C/CM(W)	Passive module with 1 USBC FF port. Input — Female USB–C Connector. Output — Male pigtail cable 40cm long. Dimensions -50 x 25 x 60mm (1.96" x 0.98" x 2.36"). Weight — 0.05 kg (0.11 lb.)